

## Quick Start Guide Bluetooth Music Receiver WM-BT18

Compatible with the following models:


- CITROEN Berlingo from year of construction 2004
- CITROEN C1 from year of construction 2004
- CITROEN C2 from year of construction 2004
- CITROEN C3 from year of construction 2004
- CITROEN C3 Picasso from year of construction 2009
- CITROEN DS3 from year of construction 2010
- CITROEN C4 from year of construction 2004
- CITROEN C4 Picasso from year of construction 2006
- CITROEN DS4 from year of construction 2011
- CITROEN C4 Aircross from year of construction 2012
- CITROEN C5 from year of construction 2004
- CITROEN DS5 from year of construction 2011
- CITROEN C6 from year of construction 2004
- CITROEN C8 from year of construction 2004
- CITROEN Nemo from year of construction 2007
- CITROEN Jumpy from year of construction 2007
- CITROEN Jumper from year of construction 2006
- PEUGEOT 1007 from year of construction 2005
- PEUGEOT 107 from year of construction 2005
- PEUGEOT 207 from year of construction 2005
- PEUGEOT 307 from year of construction 2005
- PEUGEOT 407 from year of construction 2005
- PEUGEOT 607 from year of construction 2005
- PEUGEOT 807 from year of construction 2005

- **Only in conjunction with:**

Blaupunkt RD4 N1 Radio

### Connect the adapter:

1. Remove the radio.
2. Now insert the plug of the Bluetooth Adapter WM-BT18 from the back of the Quadlock plug into chamber B until it clicks into place. This should also work if the Quadlock plug is still on the radio. If the cables are too short or you can see bad the back of the plug, you can solve the Quadlockstecker before completely from the radio.



3. Now connect the black earth cable of the WM-BT18 either to the radio housing or to the earth lead leading to the radio. Without a good ground connection, the function of the adapter is not given.
4. Now connect the red cable (ignition plus + 12V) to a switched + 12V line. Since this is usually no longer available behind the radio, you can pick up the voltage here, for example, from the cigarette lighter or the air conditioning (measurement with multimeter necessary). Ignition on = + 12V are on / Ignition off = 0V are on.
5. Establish a Bluetooth connection by activating Bluetooth pairing and searching for the ``WM`` Bluetooth device. You should then set the volume to full volume on the connected device.
6. Before reinstalling the radio, test the function of the adapter. Switch on the AUX function with the Mode button or via the menu.

**The AUX function must be enabled. If this is not the case, the activation by a specialist workshop is necessary.**

Has something been left unclear? You can reach us MO-FR, from 8-17 o'clock under the E-Mail: [service@watermark-germany.de](mailto:service@watermark-germany.de)